Vinyl Application Fluids

Description

Vinyl Application Fluids

Application Fluids & Adhesive Removers

Landor Liquid Application fluids and Adhesive removers provide much improved quality, time saving, ease and perfection when Installing Graphics to Surfaces as well as removing hard to clean Adhesive from Surfaces

default watermark



ActionTac,

- ActionTac is a ready to use vinyl application fluid for applying pressure sensitive vinyl, decals and other adhesive films to most surfaces.

â?¢ A great preparation and cleaning agentâ?¢ One product â?? works for all grades of vinylâ?¢ Will not cause any damage to transfer tape or cause separationâ?¢ Less clean-up & less residueâ?¢ No harmful odors

- **Order Here**
-

Splash

Concentrated Splash is the most cost effective application fluid on the market.

â?¢ Wets the surface allowing you to slide the graphics into placeâ?¢ Great when working with large graphicsâ?¢ Promotes faster adhesionâ?¢ 60cc. makes approximately one litre of vinyl application solution

default watermark



default watermark



Window Juice

- A window application fluid, especially adapted for Glass Surfaces, â?? designed specifically to allow users more time for easy re positioning.
  â?¢ For use with pressure sensitive vinyl graphics, decals and most adhesive films.â?¢ Eliminates bubbles and wrinkles, providing a crease free result.â?¢ Works in extreme weather conditions cold or hot, dry or warmâ?¢ Fast, simple, clean applicationâ?¢ User-friendly, safe, and easy to use
- **Order Here**

Adhesive Remover â?? Grafix Gone.

- **Grafix Gone â??** Softens adhesive residue within 90 seconds for easy removal.
  â?¢ Great for removing old paper sheeting from plasticsâ?¢ Will not damage most plasticsâ?¢ Will not harm latex paintâ?¢ No extra cleanup after removing adhesive residue
- **Order Here**

default watermark


default watermark
GRAFIX GONE
"Works FAST"
GRAFIX GONE softens adhesive residue within 90 seconds on most surfaces. May be used on vinyl banners, Plexiglas, Styrofoam, styrene, glass and all painted surfaces. Spot test on new paint before using. Will not harm latex paint.
DIRECTIONS FOR USE:
1. Use heat lamp or heat gun to soften vinyl. Pull the vinyl from the surface.
2. Apply GRAFIX GONE with sprayer, cloth or paper towel.
3. Let sit for at least 90 seconds until glue softens.
4. Scrape with squeegee to remove glue residue.
5. Wipe area with a clean cloth or towel.
6. Remove any remaining glue with GRAFIX GONE. Dry surface thoroughly.
CONTAINS 1 QUART LIQUID U.S.

Date Created
2023/06/26
Author
dlandor

default watermark